RESEARCH ARTICLE OPEN ACCESS

Multi Classifier with Grey Wolf Optimization (GWO-CKD) for Chronic Kidney Disease Classification

Walelign Tewabe Sewunetie

Department of Computer Science, Debre Markos - Ethiopia

ABSTRACT

Steady, poor quality irritation is presently treated as a significant attribute of Chronic Kidney Disease (CKD). The calculations are able in improving the predominance of expectation, examination, and infection arrangement when accurately utilized. By information strategy, such data can take out and got to adjusting the data set activities from amassing and recuperation to learning and eliminating data. This characterization cycle happens in two sections specifically the preparation cycle and testing measure. At the preparation level, the classifier will be prepared by the picked highlights of the distinguished information. At the testing level, the introduced model will characterize the concealed clinical information.

Keywords: GWO-CKD, CKD classification, Chronic Kidney Disease (CKD)

I. INTRODUCTION

Expanded acknowledgment of CKD may encourage usage of restorative procedures to defer movement of kidney work decay or forestall CKD related metabolic complexities and cardiovascular illness [1-10]. These potential points of interest ought to be weighed against the deficiency of exactness intrinsic to embracing a nonexclusive illness characterization framework. The benefits of a uniform innovation for the definition and arranging of CKD are various in the domains of government funded training, clinical consideration, observational and interventional research.

There are part favorable circumstances that this arrangement offers yet it isn't generally conceivable to discover fitting code for some illness particularly when patient starts things out an ideal opportunity to the emergency vehicle when not many or inadequate information can't give sufficient conclusion [11-15]. To pick the best trademark the projected procedure is utilize Gray Wolf Optimization (GWO) technique. Earlier the trademark decision is refined the best trademark are used to train the classifier [20-25]. The projected method misuses hybridized piece uphold vector machine (HKSVM) classifier be abused to classify the clinical information. The arrangement is made in two critical fragments, for example, the planning portion and the investigation section. In the planning fragment, the classifier is taught by the picked normal for the recognized information. In test fragment, the new clinical information is arranged. The proposed approach is executed in the foundation of MATLAB by methods for various dataset utilizing AI approaches [29-38].

II. RELATED WORKS:

s

The adaptable enough to deal with any information stockroom that utilizes information driven mining strategy. For characterizing rules in information mining requires meta-information and business space in great information on information. For information mining with the fundamental cycles and prepared through contemplating that the information and information stockroom has just gone.

From enormous measure of information base, the information mining is utilized to discover or create new helpful data's was proposed by Palani et al. [45]. To settle on significant business choices from huge data sets is the way toward separating beforehand obscure and processable data. The data offering types of assistance like on-line administrations are over the Internet and information warehousing for a few arising applications in data. The client conduct better is perceived by the information disclosure strategies for different information mining. Of an outline of information disclosure data set and information mining to expand the business openings and to improve the help gave. In various domains, for instance, tutoring, government, exchange, industry, and so forth for the field of Artificial Intelligence for data revelation and data mining. The Knowledge Discovery, Data Mining and association between Knowledge are presented. Rajagopal et al. [28] proposed Data Mining troubles, Data Mining advancement, Data mining tasks and Data mining theory.

III. PROPOSED WORK: FEATURE SELECTION

After the pre-processing stage, the characteristics from the input are selected using proposed approach. The approach of GWO is optimally used to select the characteristic of feature. Feature subset selection works by removing features that are not relevant or are redundant. One objective for both feature subset selection and feature extraction methods is to avoid overfitting the data in order to make further analysis possible. The simplest is feature selection, in which the number of gene probes in an experiment is reduced by selecting only the most significant according to some criterion such as high levels of activity. The feature choice strategy likewise incorporates the determination of subsets, assessment of subset and assessment of selected feature.

Grey Wolf Optimization

During chasing and hunting for prey, the democratic social behaviour of the grey wolves group is mimicked by GWO algorithm. Usually, 5-12 grey wolves members lived in a group. Based on the leading quality of wolves, the wolves follow a strict dominant hierarchy. The most prominent wolf α lead the entire group also β and δ is the secondary and tertiary level of the wolves [57-60]. The inspirational behaviour of proposed wolf model shows in figure 1. During prey hunting, the α wolf assisted by second and third subordinate wolves for decision making. The important steps of GWO algorithm such as prey encircling, prey hunting, exploitation and exploration for prey are discussed in upcoming section.

IV. RESULT

Here, converses the outcome acquired as of the projected method. The proposed model is executed in MATLAB platform with the windows machine including Intel Core i5 processor among 4 GB RAM with its haste 1.6 GHz. This proposed CKD classification model compared with basic SVM, Optimal-FMMNN with various performance measures by confusion matrix and some performance measures. The parameters involved in the presented algorithm are given as follows: best position: destination position, Number of search agents: 30, best score: alpha score, Maximum number of iterations: 300 and dimension as 5. The age of patient is presented in the age attribute but the Kidney disease can cause any age of the persons. The standard ranges of blood pressure consist of low and high pulse. Moreover, diastolic pressure and systolic pressure are the dual values [61-68]. The diastolic pressure only considers blood pressure. The kidney's capacity is to concentrate in the urine information provided by specific gravity. The blood has protein as Albumin.

V. CONCLUSION

This paper discussed the CKD data classification by intelligent hybrid kernel classifier, with optimal feature selection via GWO for the validation purpose only various heart disease database used, its classified by HKSVM. tentative conclusion specifies so as to the planned categorization arrangement contains surpass using surrounding improved accuracy of 97.26% for kidney chronic dataset while contrast obtainable SVM technique only accomplish 94.77% and optimal- FMMNN classifier accomplish 93.78%. In future, the presented model can be implemented in real time to assist physicians and medical organizations. Besides, the parameter tuning of proposed algorithm can also be takes place to improve the effective performance.

REFERENCES

[1] Feng, Y., Yi, J. H., & Wang, G. G. (2019). Enhanced Moth Search Algorithm for the Set-Union Knapsack Problems. IEEE Access, 7, 173774-173785.

[2] Sivaram, M., Batri, K., Amin Salih, M., &Porkodi, V. (2019). Exploiting the Local Optima in Genetic Algorithm using Tabu Search. Indian Journal of Science and Technology, 12(1), 1-13.

[3] Venkatraman, S., &Surendiran, B. (2020). Adaptive hybrid intrusion detection system for crowd sourced multimedia internet of things systems. Multimedia Tools and Applications, 79(5), 3993-4010.

[4] Sujitha, B., Parvathy, V. S., Lydia, E. L., Rani, P., Polkowski, Z., & Shankar, K. (2020). Optimal deep learning based image compression technique for data transmission on industrial Internet of things applications. Transactions on Emerging Telecommunications Technologies, e3976.

[5] Ezhilarasu, P., Krishnaraj, N., &Dhiyanesh, B. (2015). Arithmetic Coding for Lossless Data Compression–A Review. International Journal of Computer Science Trends and Technology, 3(3).

[6] Porkodi, V., Singh, A. R., Sait, A. R. W., Shankar, K., Yang, E., Seo, C., & Joshi, G. P. (2020). Resource Provisioning for Cyber–Physical–Social System in Cloud-Fog-Edge Computing Using Optimal Flower Pollination Algorithm. IEEE Access, 8, 105311-105319.

[7] Gao, D., Wang, G. G., &Pedrycz, W. (2020). Solving fuzzy job-shop scheduling problem using DE algorithm improved by a selection mechanism. IEEE Transactions on Fuzzy Systems.

[8] Sivaram, M., Mohammed, A. S., Yuvaraj, D., Porkodi, V., Manikandan, V., &Yuvaraj, N. (2019, February). Advanced expert system using particle swarm optimization based adaptive network based fuzzy inference system to diagnose the physical constitution of human body. In International Conference on Emerging Technologies in Computer Engineering (pp. 349-362). Springer, Singapore.

[9] Jiménez, A. C., García-Díaz, V., González-Crespo, R., &Bolaños, S. (2018). Decentralized Online Simultaneous Localization and Mapping for Multi-Agent Systems. Sensors, 18(8), 2612.

[10] Venkatraman, S., Surendiran, B., & Kumar, P. A. R. (2020). Spam e-mail classification for the Internet of Things environment using semantic similarity approach. The Journal of Supercomputing, 76(2), 756-776.

[11] Lydia, E. L., Raj, J. S., PandiSelvam, R., Elhoseny, M., & Shankar, K. (2019). Application of discrete transforms with selective coefficients for blind image watermarking. Transactions on Emerging Telecommunications Technologies, e3771.

[12] Ezhilarasu, P., Prakash, J., Krishnaraj, N., Kumar, D. S., Babu, K. S., &Parthasarathy, C. (2015). A Novel Approach to Design the Finite Automata to Accept the Palindrome with the Three Input Characters. Indian Journal of Science and Technology, 8(28).

[13] Devaraj, A. F. S., Elhoseny, M., Dhanasekaran, S., Lydia, E. L., & Shankar, K. (2020). Hybridization of firefly and Improved Multi-Objective Particle Swarm Optimization algorithm for energy efficient load balancing in Cloud Computing environments. Journal of Parallel and Distributed Computing.

[14] Zou, D., Wang, G. G., Sangaiah, A. K., & Kong, X. (2017). A memory-based simulated annealing algorithm and a new auxiliary function for the fixed-outline floorplanning with soft blocks. Journal of Ambient Intelligence and Humanized Computing, 1-12.

[15] Kumar, A., Ahuja, H., Singh, N. K., Gupta, D., Khanna, A., & Rodrigues, J. J. (2018). Supported matrix factorization using distributed representations for personalised recommendations on twitter. Computers & Electrical Engineering, 71, 569-577.

[16] Sivaram, M., Porkodi, V., Mohammed, A. S., Manikandan, V., &Yuvaraj, N. (2019). Retransmission DBTMA protocol with fast retransmission strategy to improve the performance of MANETs. IEEE Access, 7, 85098-85109.

[17] Venkatraman, S., & Kumar, P. A. R. (2019). Improving Adhoc wireless sensor networks security using distributed automaton. Cluster Computing, 22(6), 14551-14557.

[18] Lydia, E. L., Govindaswamy, P., Lakshmanaprabu, S., &Ramya, D. (2018). Document clustering based on text mining K-means algorithm using euclidean distance similarity. J. Adv. Res. Dyn. Control Syst.(JARDCS), 10(2), 208-214.

[19] Ortin, F., Mendez, S., García-Díaz, V., & Garcia, M. (2014). On the suitability of dynamic languages for hot-reprogramming a robotics framework: a Python case study. Software: Practice and Experience, 44(1), 77-104.

[20] Krishnaraj, N., Ezhilarasu, P., & Gao, X. Z. Hybrid Soft Computing Approach for Prediction of Cancer in Colon Using Microarray Gene Data. Current Signal Transduction Therapy, 11(2).

[21] Le Nguyen, B., Lydia, E. L., Elhoseny, M., Pustokhina, I., Pustokhin, D. A., Selim, M. M., ... & Shankar, K. (2020). Privacy Preserving Blockchain Technique to Achieve Secure and Reliable Sharing of IoT Data. CMC-COMPUTERS MATERIALS & CONTINUA, 65(1), 87-107.

[22] Chavhan, S., Gupta, D., Chandana, B. N., Khanna, A., & Rodrigues, J. J. (2019). IoT-based Context-Aware Intelligent Public Transport System in a metropolitan area. IEEE Internet of Things Journal.

[23] Gu, Z. M., & Wang, G. G. (2020). Improving NSGA-III algorithms with information feedback models for large-scale many-objective optimization. Future Generation Computer Systems, 107, 49-69.

[24] Porkodi, V., Khan, J., Mohammed, A. S., Bhuvana, J., & Sivaram, M. OPTIMIZED COOPERATIVE QOS ENHANCED DISTRIBUTED MULTIPATH ROUTING PROTOCOL.

[25] Geerthik, S., Venkatraman, S., & Gandhi, R. (2016). AnswerRank: Identifying Right Answers in QA system. International Journal of Electrical and Computer Engineering, 6(4), 1889.

[26] Samad, A., Salima, R., Lydia, E. L., & Shankar, K. (2020). Definition and Features of Rural Marketing Strategies for Encourage Development in Rural Areas. TEST Engineering & Management, 82, 4983-4988.

[27] Palani, E., Nagappan, K., &Alhadidi, B. (2016). Segmentation and Texture Analysis for Efficient Classification of Breast Tumors

from Sonograms. Current Signal Transduction Therapy, 11(2), 84-90.

[28] Rajagopal, A., Ramachandran, A., Shankar, K., Khari, M., Jha, S., Lee, Y., & Joshi, G. P. (2020). Fine-tuned residual network-based features with latent variable support vector machine-based optimal scene classification model for unmanned aerial vehicles. IEEE Access, 8, 118396-118404.

[29] Mondragon, V. M., García-Díaz, V., Porcel, C., & Crespo, R. G. (2018). Adaptive contents for interactive TV guided by machine learning based on predictive sentiment analysis of data. Soft Computing, 22(8), 2731-2752.

[30] Feng, Y., Yu, X., & Wang, G. G. (2019). A Novel Monarch Butterfly Optimization with Global Position Updating Operator for Large-Scale 0-1 Knapsack Problems. Mathematics, 7(11), 1056.

[31] Mohammed, A. S., & Sivaram, P. (2018). Securing the Sensor Networks Along With Secured Routing Protocols for Data Transfer in Wireless Sensor Networks.

[32] Geerthik, S., Venkatraman, S., & Gandhi, K. R. (2016, February). Reward rank: A novel approach for positioning user answers in community question answering system. In 2016 International Conference on Information Communication and Embedded Systems (ICICES) (pp. 1-6). IEEE.

[33] Sivaram, M., Lydia, E. L., Pustokhina, I. V., Pustokhin, D. A., Elhoseny, M., Joshi, G. P., & Shankar, K. (2020). An optimal least square support vector machine based earnings prediction of blockchain financial products. IEEE Access, 8, 120321-120330.

[34] Ghantasala, G. P., &KrishnaRaj, N. Support Vector Machine Based Automatic Mammogram Classification Using Hybrid Optimization Algorithm.

[35] Sikkandar, M. Y., Alrasheadi, B. A., Prakash, N. B., Hemalakshmi, G. R., Mohanarathinam, A., & Shankar, K. (2020). Deep learning based an automated skin lesion segmentation and intelligent classification model. Journal of Ambient Intelligence and Humanized Computing, 1-11.

[36] Zhang, Z., Wang, G. G., Zou, K., & Zhang, J. (2014). A solution quality assessment method for swarm intelligence optimization algorithms. The Scientific World Journal, 2014.

[37] Sivaram, Murugan et al. 'Data Fusion Using Tabu Crossover Genetic Algorithm in Information Retrieval'. 1 Jan. 2020 : 1 – 10.

[38] Khamparia, A., Pandey, B., Tiwari, S., Gupta, D., Khanna, A., & Rodrigues, J. J. (2020). An integrated hybrid CNN–RNN model for visual description and generation of captions. Circuits, Systems, and Signal Processing, 39(2), 776-788.

[39] Geerthik, S., Gandhi, K. R., &Venkatraman, S. (2016, December). Domain expert ranking for finding domain authoritative users on community question answering sites. In 2016 IEEE International Conference on Computational Intelligence and Computing Research (ICCIC) (pp. 1-5). IEEE.

[40] Muruganantham, A., Nguyen, P. T., Lydia, E. L., Shankar, K., Hashim, W., &Maseleno, A. (2019). Big data analytics and intelligence: A perspective for health care.

[41] Ramkumar, V., &Krishnaraj, N. Weight Based LSA to Retrieve Information from Web Pages Based On Document Score.

[42] Balakiruthiga, B., Deepalakshmi, P., Mohanty, S. N., Gupta, D., Kumar, P. P., & Shankar, K. (2020). Segment routing based energy aware routing for software defined data center. Cognitive Systems Research.

[43] Chu, H. C., Wang, G. G., & Deng, D. J. (2016). The social networking investigation of metadata of forensic artifacts of a typical WeChat session under Windows. Security and Communication Networks, 9(18), 5698-5709.

[44] Sivaram, M., Yuvaraj, D., Mohammed, A. S., Manikandan, V., Porkodi, V., &Yuvaraj, N. (2019). Improved Enhanced Dbtma with Contention-Aware Admission Control to Improve the Network Performance in Manets. CMC-COMPUTERS MATERIALS & CONTINUA, 60(2), 435-454.

[45] Gochhayat, S. P., Lal, C., Sharma, L., Sharma, D. P., Gupta, D., Saucedo, J. A. M., &Kose, U. (2019). Reliable and secure data transfer in IoT networks. Wireless Networks, 1-14.

[46] Subbarayalu, V., Surendiran, B., &Arun Raj Kumar, P. (2019). Hybrid Network Intrusion Detection System for Smart Environments Based on Internet of Things. The Computer Journal, 62(12), 1822-1839.

[47] Rosa, A. T. R., Pustokhina, I. V., Lydia, E. L., Shankar, K., & Huda, M. (2019). Concept of electronic document management system (EDMS) as an efficient tool for storing document. Journal of Critical Reviews, 6(5), 85-90.

[48] Espada, J. P., Diaz, V. G., Crespo, R. G., Bustelo, B. C. P. G., &Lovelle, J. M. C. (2015). An intelligent Mobile Web Browser

to adapt the mobile web as a function of the physical environment. IEEE Latin America Transactions, 13(2), 503-509.

[49] Kumar, R. S., Krishnaraj, N., &Keerthana, G. (2017). Assessment of Quality of Service in Communication Network and Evaluating Connectivity Among IP Networks. Asian Journal of Applied Science and Technology (AJAST), 1(3), 319-322.

[50] Elhoseny, M., Rajan, R. S., Hammoudeh, M., Shankar, K., &Aldabbas, O. (2020). Swarm intelligence–based energy efficient clustering with multihop routing protocol for sustainable wireless sensor networks. International Journal of Distributed Sensor Networks, 16(9), 1550147720949133.

[51] Chu, H. C., Wang, G. G., & Park, J. H. (2015). The digital fingerprinting analysis concerning google calendar under ubiquitous mobile computing era. Symmetry, 7(2), 383-394.

[52] Manikandan, V., Sivaram, M., Mohammed, A. S., &Porkodi, V. (2020). Nature Inspired Improved Firefly Algorithm for Node Clustering in WSNs. CMC-COMPUTERS MATERIALS & CONTINUA, 64(2), 753-776.

[53] Kuppusamy, P., Venkatraman, S., Rishikeshan, C. A., & Reddy, Y. P. (2020). Deep learning based energy efficient optimal timetable rescheduling model for intelligent metro transportation systems. Physical Communication, 101131.

[54] Asih, E. S., Nguyen, P. T., Lydia, E. L., Shankar, K., Hashim, W., &Maseleno, A. (2019). Mobile E-commerce website for technology-based buying selling services. International Journal of Engineering and Advanced Technology, 8(6), 884-888.

[55] Lydia, E. L., &Swarup, M. B. (2015). Big data analysis using hadoop components like flume, mapreduce, pig and hive. International Journal of Science, Engineering and Computer Technology, 5(11), 390.

[56] Sengar, S. S., Hariharan, U., &Rajkumar, K. (2020, March). Multimodal Biometric Authentication System using Deep Learning Method. In 2020 International Conference on Emerging Smart Computing and Informatics (ESCI) (pp. 309-312). IEEE.

[57] Maseleno, A., Hashim, W., Perumal, E., Ilayaraja, M., & Shankar, K. (2020). Access control and classifier-based blockchain technology in e-healthcare applications. In Intelligent Data Security Solutions for e-Health Applications (pp. 151-167). Academic Press.

[58] Li, J., Lei, H., Alavi, A. H., & Wang, G. G. (2020). Elephant Herding Optimization: Variants, Hybrids, and Applications. Mathematics, 8(9), 1415.

[59] Mohammed, A. S., Kareem, S. W., Al Azzawi, A. K., & Sivaram, M. (2018). Time series prediction using SRE-NAR and SRE-ADALINE. Journal of Advanced Research in Dynamical and Control Systems, Pages, 1716-1726.

[60] Shankar, K., Elhoseny, M., Chelvi, E. D., Lakshmanaprabu, S. K., & Wu, W. (2018). An efficient optimal key based chaos function for medical image security. IEEE Access, 6, 77145-77154.

[61] Geerthik, S., Gandhi, R., &Venkatraman, S. (2006). CATEGORY BASED EXPERT RANKING: A NOVEL APPROACH FOR EXPERT IDENTIFICATION IN COMMUNITY QUESTION ANSWERING.

[62] Laxmi, C. V., &Somasundaram, K. (2014). Application Level Scheduling (AppLeS) in Grid with Quality of Service (QoS). International Journal of Grid Computing & Applications, 5(2), 1.

[63] Kumar, R. S., Krishnaraj, N., &Keerthana, G. Highly Energy Efficient and Scalable Distributed Clustering Procedure for Dense Wireless Sensor Networks.

[64] Krishnaraj, N., Kumar, K. A., & Kumar, P. K. (2018). DESIGN OF ADAPTIVE SCHEDULER TO IMPROVE PERFORMANCE OF COMPUTATIONAL GRIDS. International Journal of Pure and Applied Mathematics, 119(18), 1741-1751.

[65] Shankar, K., & Eswaran, P. (2016, January). A new k out of n secret image sharing scheme in visual cryptography. In 2016 10th International Conference on Intelligent Systems and Control (ISCO) (pp. 1-6). IEEE.

[66] Wei, C. L., & Wang, G. G. (2020). Hybrid Annealing Krill Herd and Quantum-Behaved Particle Swarm Optimization. Mathematics, 8(9), 1403.

[67] Sivaram, M., Yuvaraj, D., Mohammed, A. S., &Porkodi, V. Estimating the Secret Message in the Digital Image. International Journal of Computer Applications, 975, 8887.

[68] Nieto, Y., Gacía-Díaz, V., Montenegro, C., González, C. C., & Crespo, R. G. (2019). Usage of machine learning for strategic decision making at higher educational institutions. IEEE Access, 7, 75007-75017.